Serial No. 10/695,453 Docket No. T36-159874M/SW (NGB.322) 2

AMENDMENTS TO THE CLAIMS:

Claim 1 is canceled without prejudice or disclaimer.

- 1. (Canceled).
- 2. (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer, comprising:

a film including a polycrystalline metal disposed on said Group III nitride compound semiconductor layer.

wherein said polycrystalline metal comprises a transition metal, and

An electrode for a p-type Group III nitride compound semiconductor layer according to claim-1;

wherein said polycrystalline metal comprises a fiber structure in which crystal planes of crystal grains are oriented.

- (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer according to claim <u>24-1</u>, wherein said polycrystalline metal comprises large crystal grains.
- 4-6. (Canceled).
- 7. (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer, comprising:

Serial No. 10/695,453

Docket No. T36-159874M/SW

(NGB.322)

a film including a polycrystalline metal disposed on said Group III nitride compound semiconductor layer,

3

wherein said polycrystalline metal comprises a transition metal, and

The electrode according to claim 1,

wherein the polycrystalline metal comprises a fiber structure in which a crystal grain boundary density decreases such that a quantity of defects in the metal/semiconductor boundary decreases.

- 8. (Previously presented) The electrode according to claim 2, wherein a percentage of oriented crystal grains occupying said fiber structure is increased to provide an increase of an orientation force of the metal film.
- 9. (Previously presented) The electrode according to claim 2, wherein said fiber structure comprises a predetermined percentage of oriented crystal grains to provide a predetermined orientation force of the metal film.
- 10. (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer, comprising:

a film including a polycrystalline metal disposed on said Group III nitride compound semiconductor layer,

wherein said polycrystalline metal comprises a transition metal, and

The electrode-according to claim 1,

wherein the polycrystalline metal comprises a fiber structure including oriented crystal faces including closed packed planes.

Serial No. 10/695,453 Docket No. T36-159874M/SW

(NGB.322)

11. (Previously presented) An electrode for a p-type Group III nitride compound semiconductor layer, the electrode comprising:

4

a polycrystalline metal film disposed on said p-type Group III nitride compound semiconductor layer to form a metal/semiconductor boundary,

wherein said polycrystalline metal film comprises a fiber structure in which a crystal grain boundary density decreases such that a quantity of defects in the metal/semiconductor boundary decreases, and

wherein said polycrystalline metal film comprises a transition metal.

- 12. (Previously presented) The electrode according to claim 11, wherein said fiber structure of said polycrystalline metal film comprises oriented crystal planes of crystal grains.
- 13. (Previously presented) The electrode according to claim 11, wherein said polycrystalline metal comprises crystal grains of a predetermined large size.
- 14. (Previously presented) The electrode according to claim 12, wherein a percentage of oriented crystal grains occupying said fiber structure is increased to provide an increase of an orientation force of the metal film.
- 15. (Previously presented) The electrode according to claim 11, wherein the polycrystalline metal comprises a fiber structure including oriented crystal faces including closed packed planes.

Serial No. 10/695,453 Docket No. T36-159874M/SW

(NGB.322)

16. (Previously presented) The electrode according to claim 11, wherein said p-type Group III nitride compound semiconductor layer comprises one of GaN, AlGaN, and GaInN.

5

- 17. (Previously presented) The electrode according to claim 11, wherein said polycrystalline metal comprises one of platinum (Pt), nickel (Ni), palladium (Pd), chromium (Cr), and iron (Fe).
- 18. (Previously presented) The electrode according to claim 11, wherein a degree of said crystal grains of said predetermined large size is no less than a thickness of said polycrystalline metal film.
- 19. (Previously presented) A p-type Group III nitride compound semiconductor lightemitting device, comprising:

an electrode including a polycrystalline metal film disposed on a p-type Group III nitride compound semiconductor layer of said light-emitting device to form a metal/semiconductor boundary,

wherein said polycrystalline metal film comprises a fiber structure in which a crystal grain boundary density decreases such that a quantity of defects in the metal/semiconductor boundary decreases, and

wherein said polycrystalline metal film comprises a transition metal.

Serial No. 10/695,453 Docket No. T36-159874M/SW

(NGB.322)

20. (Previously presented) The device according to claim 19, wherein said fiber structure of said polycrystalline metal film comprises oriented crystal planes of crystal grains.

6

- 21. (Previously presented) The device according to claim 19, wherein said polycrystalline metal comprises crystal grains of a predetermined large size.
- 22. (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer, comprising:

a film including a polycrystalline metal disposed on said Group III nitride compound semiconductor laver.

wherein said polycrystalline metal comprises a transition metal, and

The electrode according to claim 1,

wherein said polycrystalline metal comprises one of platinum (Pt), nickel (Ni), palladium (Pd), chromium (Cr), and iron (Fe).

- 23. (Previously presented) The p-type Group III nitride compound semiconductor light-emitting device according to claim 19, wherein said polycrystalline metal comprises one of platinum (Pt), nickel (Ni), palladium (Pd), chromium (Cr), and iron (Fe).
- 24. (Currently amended) An electrode for a p-type Group III nitride compound semiconductor layer, comprising:

a film including a polycrystalline metal disposed on said Group III nitride compound semiconductor layer.

wherein said polycrystalline metal comprises a transition metal, and

Serial No. 10/695,453 Docket No. T36-159874M/SW (NGB.322)

The electrode according to claim 1,

wherein said film is disposed directly on said p-type Group III nitride compound semiconductor layer.

7